

IMPROVEMENTS IN OR RELATING TO EMERGENCY LIGHTING

Background of the Invention

- 5 This invention concerns improvements in or relating to emergency lighting, especially emergency lighting used to indicate an escape path leading to an exit for evacuation of a passenger vehicle in an emergency, for example following an accident.
- 10 The invention has particular application to passenger vehicles of the type in which rows of seats are provided on either side of an aisle with an exit at one or both ends of the aisle and/or on one or both sides of the aisle between the ends. Examples of this type of passenger vehicle include aircraft, trains and coaches.
- 15 Vehicles of this type are designed to carry a large number of passengers in a confined space. For example, each row may seat two or three passengers on each side of the aisle which is normally only wide enough for one passenger to move along between the aisle seats.
- 20 As a result, there may be several passengers in each row who have to access the aisle one at a time and move along the aisle to an exit. Furthermore, as passengers move along the aisle, they obstruct and restrict access to the aisle of other passengers in the rows. It will be
- 25 understood therefore that passengers must keep moving along the aisle towards the exit(s) to evacuate the vehicle in an efficient, orderly manner. Accordingly, there is a need to ensure that passengers can find their way to the exit(s) easily and reliably.
- 30 In most vehicles of this type, an electrical lighting system is fitted at ceiling level which provides sufficient lighting for passengers to evacuate

the vehicle under normal circumstances. However, in an emergency following an accident, the electrical lighting system may be inoperable if the electrical connections to the power source are damaged. For example, the electrical connections may be broken by impact damage to the structure of the vehicle or by outbreak of a fire following a crash. Moreover, even if the lighting system remains operable, the outbreak of fire may render the lighting system ineffective if the light is blocked by smoke filling the interior of the vehicle.

- 10 The lighting system may also fail in other circumstances without an accident due to faults arising in normal service making it difficult for passengers to leave the vehicle safely at night or in conditions of low ambient light.
- 15 For these reasons, it is desirable, and in the case of aircraft mandatory, to provide an emergency lighting system as a back-up to the normal lighting system. Typically, such emergency lighting is provided at floor level and identifies the path leading to the exit(s) for passengers to follow. In this way, if the interior of the vehicle fills with smoke, the emergency lighting is below the smoke level allowing passengers to crawl to the exit(s) along the path illuminated by the emergency lighting.
- 20

Traditionally, such emergency lighting has been electrical with the wiring and power source separate from that of the lighting system provided at ceiling level for normal use. The provision of a separate emergency lighting system adds considerably to the costs for initial installation and subsequent maintenance in service with regular checks to ensure operability. In the case of aircraft, the system must be checked each time before take-off and the aircraft is grounded if any repairs are required.

25

30 The resulting delay is inconvenient for passengers and adds to the running

cost for the aircraft operator, especially if a take-off slot has to be vacated.

5 A further problem of such electrical emergency lighting systems is the extra weight of the storage batteries normally employed as the separate power source which adds to operating costs. Thus, fuel costs may be increased and/or, in the case of aircraft, the number of passengers may have to be reduced to compensate for the extra weight.

10 The most important disadvantage of the known electrical emergency lighting systems however, is probably that they suffer from the same problem of the electrical connections being broken in a crash resulting from structural damage to the vehicle and/or from fire. Accordingly, such emergency lighting systems can be rendered inoperative just at the
15 very time they are required to assist passengers to evacuate the vehicle.

It is desirable therefore to provide an emergency lighting system which does not depend on electrical connections to a power source to provide the required level of illumination. One such system for use in an aircraft
20 is described in our UK Patent No.2 314 536 in which the path to the exit(s) is illuminated by photoluminescent material incorporated into a track extending along the aisle for passengers to follow to the exit(s). The photoluminescent material is chosen to provide an acceptable level of illumination over a period of time sufficient for the passengers to
25 evacuate the aircraft.

The emergency lighting system described in our afore-mentioned patent has met with considerable success due to the many benefits and advantages for both the manufacturer and operator of aircraft in which the
30 system is fitted. Thus, the system does not require connection to a power

source thereby eliminating completely the wiring and separate storage batteries required for conventional electrical emergency lighting systems.

In one arrangement, the track comprises an outer housing and an insert
5 provided with the photoluminescent material received within the outer housing. The outer housing includes a base and a separate cover which are releasably connected together to locate and retain the insert. The base and cover are made of plastics such as polycarbonate with at least the cover being transparent or translucent to allow the light emitted by the
10 photoluminescent material to pass through.

By forming the track in this way, when a cover is worn or damaged in service, a replacement cover can be fitted to the existing base and insert allowing the track to be repaired with minimum delay and disruption. In
15 this way, cost savings can be made for maintenance of the track. There can be occasions, however, when it is more convenient to replace the entire track, for example during refurbishment of an aircraft, and in these circumstances the insert may be recovered and re-used. This may allow further cost savings to be made.

20

Summary of the Invention

The present invention seeks to provide further improvements to our existing photoluminescent track for use in emergency lighting systems for
25 passenger vehicles and in particular for aircraft.

More particularly, the present invention concerns a photoluminescent track that is of simple construction that facilitates manufacture and assembly.

30

According to a first aspect of the invention, there is provided a method of manufacturing a photoluminescent track for an emergency lighting system comprising providing an elongate hollow outer member and an elongate inner member having photoluminescent material on at least one side, and
5 push-fitting the inner member in the outer member from one end.

By this invention, the base and cover of our existing track are replaced by a single component integrally formed, for example by moulding or extrusion, whereby assembly of the track is facilitated by allowing the
10 inner member to be slid lengthwise of the outer member from one end.

The outer member is made of a light transmitting material and the inner member is made of a material that is sufficiently rigid to be push fitted in the outer member. For example, the outer member may be made of
15 transparent or translucent plastics such as polycarbonate and the inner member may be made of metal, for example aluminium strip, coated on at least one side with photoluminescent material.

Advantageously, the outer member is formed with an internal longitudinal slot open at one or both ends for inserting the inner member and the
20 method further includes sealing the inner member within the slot. For example, by attaching a closure such as an end cap or foil strip across the open end(s) of the slot. In this way, ingress of dirt or moisture that may affect the life and/or performance of the photoluminescent material is
25 prevented.

The inner member may be removable from the outer member. For example, we may secure the closure with a sealant/adhesive material such as silicone that allows the closure to be detached when it is desired to
30 remove the inner member. In this way, the inner member may be separated from the outer member and re-used, for example if the outer

member is damaged or worn and has to be replaced. Additionally, where the upper surface of the outer member is damaged or worn, the inner member may be removed and re-inserted the other way up enabling the track to be re-fitted with the lower surface now uppermost. In this way,
5 the life of the track can be extended by reversing the orientation of the outer member to present a new, clean surface uppermost.

Alternatively, we may provide photoluminescent material on both sides of the inner member. In this way, the track can be laid with either side of
10 the outer member uppermost without removing and re-fitting the inner member the other way up. This arrangement also enables the life of the track to be extended if the side that is uppermost initially becomes worn or is damaged.

15 According to a preferred feature of the invention, the outer member is compressed in a direction transverse to its length after the inner member has been inserted to reduce the depth of the track and axially locate the inner member within the outer member.

20 Such compression may be effected by any suitable means, for example the assembled track may be passed between a pair of pressure rollers engaging the top and bottom surfaces of the outer member or placed in a press. The compression may be applied across the full width of the track or it may be restricted to selected regions only, for example along both
25 edges.

We may pre-heat the track prior to compressing the outer member. Such pre-heating may soften the outer member sufficiently to facilitate the compression of the outer member. Alternatively, we may cold form the
30 outer member by applying the compression without pre-heating.

The compression may be employed to apply a pattern to the surface of the track. For example, we may employ rollers having grooves in the peripheral surface that form ribs in the surface of the outer member on one or both sides. The pattern may be decorative and/or provide the track with an anti-slip surface to reduce the risk of accidents.

According to a second aspect of the invention, we provide a photoluminescent track for an emergency lighting system comprising an elongate hollow outer member having first and second major wall portions connected by opposed side wall portions to define a longitudinally extending slot, and an elongate inner member extending lengthwise of the slot and having photoluminescent material on one side covered by one of the major wall portions of the outer member, wherein the inner member is a push-fit from one end of the slot for assembly of the track, and said one major wall portion of the outer member is made of a material to transmit light emitted by the photoluminescent material.

By this invention, the inner member provided with the photoluminescent material is enclosed and surrounded along the length of the track by the outer member which is formed in one piece. In this way, there are fewer parts for assembly of the track and there is less risk of dirt or liquid being trapped by the outer member. As a result savings in the cost and time for assembly, cleaning and maintenance of the track can be achieved.

The slot is preferably closed by a closure such as an end cap or a thin strip of a material such as metal foil attached to the outer member with a sealant/adhesive material such as silicone or any other suitable means. In this way, the slot is sealed to retain the inner member within the outer member and the closure can be removed if it is desired to remove the inner member. Furthermore, the provision of the closure does not

significantly alter the length of the outer member allowing discrete lengths of track to be butted together.

5 In a preferred arrangement, the outer member is formed with the slot open at both ends. For example, the outer member may be an extrusion and cut to any desired length. The inner member can then be inserted from either end of the outer member and both ends of the slot closed by attaching a closure to seal the inner member in the outer member.

10 In an alternative arrangement, the outer member is formed with the slot open at one end and closed at the other end. For example, the outer member may be a moulding of pre-determined length. The inner member can then be inserted from one end only which is closed by attaching a closure to seal the inner member in the outer member. With this
15 arrangement only one closure is required.

The inner member is preferably the same or substantially the same length as the outer member. In this way, discrete lengths of the track can be butted end to end with no perceptible break in the light emitted between
20 adjoining lengths of the track. More preferably, the inner member is the same or substantially the same length and substantially the same width as the outer member. In this way, light is emitted over substantially the whole surface area of one of the major wall portions of the track.

25 Advantageously, the outer member is made of transparent or translucent plastics material such as polycarbonate although it will be understood that other plastics materials may be used. Preferably, the plastics material forms a substantially rigid outer member which can withstand loads applied to the track, for example people walking on the track, and which
30 is resistant to cleaning fluids or other liquids which may come into

contact with the track. The plastics material may also be fire resistant to reduce or prevent the generation of smoke or hazardous fumes.

5 The inner member preferably comprises a base of sheet metal such as aluminium provided on one side with a layer of photoluminescent material and an optional fluid protective cover layer on top of the photoluminescent layer. A light coloured base layer may be provided under the photoluminescent layer. By the use of a metal base, the inner member is sufficiently rigid for push fitting in the slot from one end of
10 the outer member even where the outer member is of long length. Furthermore, the inner member can be made relatively thin which in turn allows the depth of the outer member to be kept to a minimum. As a result, the track may be produced with a low profile which enables the same track to be used in carpeted and non-carpeted areas of a vehicle.

15 The inner member is slidable lengthwise of the slot for push fitting the inner member during assembly. The inner member may be removed from the slot in a similar manner. In this way, the inner member may be recovered and re-used if the outer member is worn or damaged and has to
20 be replaced.

Preferably the outer member is symmetrical enabling the outer member to be laid either way up. In this way, the track may be repaired by lifting a damaged section, removing and refitting the inner member the other way
25 up and replacing the track so that the underside is now uppermost to provide a new, clean surface over the photoluminescent material of the inner member.

Alternatively, we may provide photoluminescent material on both sides of
30 the inner member. As a result, the track can be fitted either way up

without removing and re-fitting the inner member. In this way, a repair can be effected more easily.

5 The major wall portions of the outer member may have substantially planar outer surfaces. Alternatively, the outer surface of at least that major wall portion overlaying the photoluminescent material may be provided with formations having anti-slip characteristics. The formations may be restricted to the side edge regions so as not to interfere with the transmission of light emitted by the photoluminescent material. For
10 example, the formations may comprise a series of axially spaced transverse ribs of v-shape.

15 The assembled track may be subjected to a post forming operation to compress the outer member in a direction transverse to the length and thereby reduce further the depth of the track. The post forming may be carried out by passing the track between a pair of pressure rollers which may also apply formations for the anti-slip properties to the outer surface of the track. The post forming may be effected with or without pre-heating to soften the outer member for conforming to the reduced
20 thickness.

The track may be retro-fitted to a vehicle after manufacture either to provide an emergency lighting system or to replace an existing emergency lighting system. Alternatively or additionally, the track may be fitted as
25 original equipment during manufacture of a vehicle.

Where the track is fitted as original equipment, it may be pre-assembled to components for assembly of the vehicle. For example, for installation of the track on the floor of the vehicle, it is envisaged that the track may
30 be attached to the floor panels for assembly of the vehicle. The track may be manufactured in pre-determined lengths corresponding to the size

of the floor panels. In this way, the track is built-in during assembly of the vehicle and a separate assembly operation to install the emergency lighting system is avoided.

5 Thus, according to a third aspect of the invention, we provide a component for use in the construction of a vehicle wherein the component is provided with a photoluminescent track to define an escape route in the assembled vehicle.

10 Preferably, the component is a floor panel employed in the construction of an aircraft and the photoluminescent track is arranged to extend on one side of an aisle leading to an exit. More preferably, the floor panel is provided with a pair of laterally spaced photoluminescent tracks that are arranged to extend on opposite sides of the aisle to identify the boundaries
15 of the aisle and define an escape path between the tracks leading to the exit. In a preferred arrangement, the component is provided with the photoluminescent track according to the second aspect of the invention.

According to a fourth aspect of the invention, we provide a vehicle,
20 preferably an aircraft, having rows of seats on either side of an aisle, and a photoluminescent track according to the second aspect of the invention extending along each side of the aisle to identify the boundaries of the aisle and define therebetween an escape path leading to an exit at one or both ends of the aisle and/or between the ends of the aisle.

25

Preferably, the photoluminescent track is mounted on the floor and is substantially continuous along each side of the aisle leading to an exit. In this way, the escape route is not obscured by people moving along the aisle between the tracks. As a result, there is less risk of people leaving
30 the aisle and becoming trapped between the rows of seats.

Advantageously, the track includes markings to indicate the route to an exit. For example, the track may be provided with arrows or similar direction indicators to show where an exit aisle leads from the main central aisle to an exit. Alternatively or additionally, the word "exit" or the like may be provided in the track. Some form of direction indicator is generally preferred however as avoiding problems with language and/or reading words.

The markings may be formed with photoluminescent material on the inner member so as to emit light of a different colour to the rest of the track. In this way, the light output from the track is not reduced by the provision of the markings. This feature of the markings assists the smooth, continuous movement of passengers towards the exit thereby facilitating the evacuation of the vehicle in an emergency.

Typically, on each side of the aisle, the seats in each row are provided by a demountable multi-seat unit allowing the number and arrangement of seats to be altered. For example, seat units comprising two, three or four seats may be provided. These units are normally of different width with the result that the width of the aisle between seat units on each side can change when one seat unit is replaced by another seat unit with more or less seats. This can lead to problems where an emergency lighting system is provided by a floor mounted track. In particular, if a wider seat unit is fitted which extends over the track, the escape path may be concealed.

The position of the floor mounted track is fixed on installation of the emergency lighting system and, to accommodate changes in the seating layout, it is preferred to provide the seat units with a photoluminescent track on the side of the aisle seat, preferably close to the floor. The track on the aisle seats is provided in addition to the existing floor track and will provide an escape route for passengers to follow where the floor

track is concealed by the seat unit. In this way, the appearance of a substantially continuous track along each side of the aisle leading to an exit may be maintained without modification to the floor track.

- 5 Thus according to a fifth aspect of the invention, we provide in or for an aircraft having rows of seats on each side of an aisle and a photoluminescent track extending along each side of the aisle at or near floor level, at least one row including a demountable multi-seat unit on at least one side of the aisle such that the width of the aisle may be altered
- 10 by fitting any selected one of a plurality of demountable multi-seat units of different width, wherein a photoluminescent track is provided on that side of the multi-seat unit which, in use, is arranged adjacent to the aisle.

- Preferably, the track comprises a strip of photoluminescent material overlaid by a cover of transparent or translucent material attached to the
- 15 seat unit to locate and retain the photoluminescent strip in place. The photoluminescent strip may be the same or similar to the inner member of the track according to the second aspect of the invention.

- 20 Embodiments of the invention will now be described in more detail by way of example with reference to the accompanying drawings.

Brief description of the drawings

- 25 **Figure 1** is a perspective view of a track according to the present invention;

Figure 2 is an end view of the track shown in Figure 1;

- 30 **Figure 3** is a side view of the track shown in Figure 1;

Figure 4 is a plan view of the track shown in Figure 1;

Figure 5 is an enlarged cross section of the insert of the track shown in Figure 1;

5

Figures 6a through 6e are perspective views of one end of the track shown in Figures 1 to 5 showing an alternative method of sealing the track using end caps;

10

Figure 7 is an end view similar to Figure 3 showing a modification to the track of Figures 1 to 5;

Figure 8 is a plan view of the track shown in Figure 7;

15

Figure 9 is an enlarged cross-section of a modified insert;

Figure 10 shows a general arrangement of an emergency lighting system incorporating the track of Figures 1 to 5 in an aircraft;

20

Figure 11 shows a detail of the emergency lighting system shown in Figure 10 in the region of an emergency exit;

Figures 12a through 12f show examples of various markings that can be incorporated in the track of the present invention;

25

Figures 13a through 13d are perspective views showing the method of attaching the markings;

30

Figure 14 shows schematically the general arrangement of an emergency lighting system incorporating the track of Figures 1 to 5 in an aircraft having interchangeable seat units; and

Figure 15 shows a detail of the aisle seat of an interchangeable seat unit for the emergency lighting system of Figure 14.

5 Detailed description of the exemplary embodiments

Referring first to Figures 1 to 5 of the drawings, a photoluminescent track 1 is shown comprising an elongate hollow housing 2 of uniform, generally rectangular cross-section and an elongate insert 3. The housing 2 has flat upper and lower walls 2a and 2b respectively connected by opposed side walls 2c, 2d to define therebetween a substantially rectangular slot 4.

The insert 3 has a width 'w' and thickness 't' slightly less than the corresponding dimensions of the slot 4 to provide limited clearance for push-fitting the insert 3 in the slot 4 from one end of the housing 2. The insert 3 extends the length of the slot 4 between the ends of the housing 2 and the width of the slot 4 between the sides of the housing 2.

The dimensions of the housing 2 and insert 3 are chosen so that the insert 3 emits light over a major part, preferably at least 75% and more preferably at least 90%, of the surface of the upper wall 2a of the housing 2 overlying the photoluminescent material.

As best shown in Figure 4, the insert 3 comprises a base 3a of sheet aluminium covered on one side by a layer 3b of photoluminescent material overlaid with a fluid protective layer 3c of clear plastics or lacquer. The use of aluminium for the base 3a has advantages over the vinyl base employed for the insert described in our earlier patent.

In particular, we have found that adhesion of the layer 3b of photoluminescent material is improved and that chemical interaction between the insert 3 and the housing 2 is eliminated or significantly reduced. We have also found that using aluminium for the base 3a in place of vinyl improves the fire resistance and/or smoke generation characteristics of the insert 3.

In this embodiment, the photoluminescent material emits a green or yellow-green light that is visible when the level of ambient light from natural or artificial light sources is low. It will be understood that photoluminescent material which emits other colours of light may be employed. Further details of suitable photoluminescent materials are provided in our afore-mentioned earlier patent the disclosure of which is incorporated herein by reference.

The housing 2 is a one piece moulding of a rigid plastics such as polycarbonate which transmits the light emitted by the photoluminescent material. The plastics may also be fire resistant. In this embodiment, the housing 2 is formed in lengths of 1 metre which may be cut into shorter lengths as desired for any required application.

It will be understood, however, that the housing 2 can be formed in longer or shorter lengths and in fact a range of standard lengths may be provided for selection and fitment in the appropriate combination for any given installation. Alternatively, the housing 2 may be formed by extrusion and cut to the required length for assembly with the insert 3.

The insert 3 is cut to the length of the housing 2 and is a push-fit in the slot 4 from one end of the housing 2 with the layer 3b of photoluminescent material uppermost. The insert 3 is sufficiently rigid by virtue of forming the base 3a from sheet aluminium to allow push

fitting for any length of housing 2. In addition, the strength/rigidity required for push-fitting the insert 3 can be achieved with relatively thin sheet material allowing the track 1 to be produced with a low profile. This is a further advantage of using aluminium for the base 3a in place of vinyl.

The insert 3 is enclosed and surrounded by the housing 2 along the length of the track and the slot 4 is closed at each end by attaching a thin strip of metal foil (not shown) or similar sheet material to the end faces of the housing 1. For example, the metal foil may be bonded by an adhesive sealant such as silicone or any other suitable means.

In this way, the slot 4 is sealed to prevent ingress of dirt or fluids and the insert 3 is encapsulated within the housing 2 when the track 1 is in use. Moreover, when the track 1 is replaced, the insert 3 can be removed by detaching or rupturing the foil and sliding the insert 3 out of the housing 2 allowing the insert 3 to be re-used.

Furthermore, if the upper surface 2a of the housing 2 is damaged or becomes worn (scratched or scuffed), a repair can be effected by lifting the appropriate section of the track 1, removing the insert 3 and re-fitting it the other way up within the housing 2. The section of track 1 can then be re-fitted with the damaged or worn upper surface 2a facing down and the lower surface 2b facing up.

25

In this way, the track 1 can be provided with a new clean, upper surface by reversing the orientation of the damaged section of track 1. As a result, the life of the track 1 can be extended and a repair carried out using the existing track 1. This is of particular benefit if a repair is required and there is no stock of spare parts available to replace the damaged section of track 1.

30

Referring now to Figures 6a through 6e there is shown an alternative method of sealing the track 1 in which the slot 4 is closed at each end (one end only shown) by a respective end cap 50 secured to the housing 2.

Each end cap 50 is similar and comprises a face plate 50a sized to match the cross-section of the housing 2 and an integral tongue 50b sized to fit within the slot 4 below the insert 3. As a result, the end caps 50 do not increase significantly the length of the housing 2 or block the absorption/emission of light by the insert 3.

The end caps 50 are secured by applying a continuous bead 51 of sealant adhesive such as silicone to bond the face plate 50a to the end of the housing 2. In this way, the slot 4 is sealed to prevent ingress of dirt or fluids and the insert 3 is encapsulated within the housing 2.

The sealant adhesive employed enables the end caps 50 to be prised off if it is required to remove the insert 3 for re-use or re-furbishment as described previously.

Referring now to Figures 7 and 8, a further modification to the above-described track 1 is shown in which like reference numerals in the series 100 are used to indicate corresponding parts.

The track 101 again comprises a housing 102 and an insert 103 received in a longitudinal slot 104 within the housing 102 by push fitting from one end as described for the previous embodiment.

The housing 102 is then compressed in a direction transverse to the length following insertion of the insert 103 by passing each side of the

assembled track 101 between a pair of rollers 105,106. Strips of metal foil or end caps (not shown) are attached to the ends of the housing 102 as described previously to seal the insert 103 within the housing 102.

- 5 The compression force is controlled to partially flatten the sidewalls 102c, 102d of the housing 102 and take-up the clearance space 107 between the insert 103 and the upper and lower walls 102a, 102b of the housing 102. As a result, the insert 103 is located between the upper and lower walls 102a, 102b and is fully encapsulated
10 by the housing 102.

In Figure 7, the solid lines show the assembled track 101 prior to compression between the rollers 105,106 and the broken lines show the assembled track 101 after compression between the rollers 105,106. As
15 shown, the depth ' d_2 ' of the housing 102 is reduced compared to the depth ' d_1 ' of the housing 102 as initially formed. In this way, the finished track 101 has a low profile suitable for use with floor coverings of different thickness butted up against the side edges.

- 20 This reduction in depth may be accompanied by a slight increase in the width of the housing 102 compared to the width as initially formed due to the local thickening of sidewalls 102c,102d. Alternatively, we may prevent any increase in the width of the housing 102 by providing stops (not shown) on each side of the housing 102 where it is compressed
25 between the rollers 105,106.

The assembled track 101 may be cold formed by passage between the rollers 105,106. Alternatively, the assembled track 101 may be pre-heated prior to passage between the rollers 105,106. The level of pre-
30 heating may be chosen to soften the plastics material of the housing 102 sufficiently to assist compression of the sidewalls 102c,102d and then

cooling the track 101 to set the plastics material in the new, flatter configuration. For example, where the housing 102 is made of polycarbonate, we may pre-heat the track to approximately 130°C prior to passing between the rollers 105,106 followed by air or water cooling.

5

In accordance with a preferred feature of this embodiment, the upper rollers 105 are formed with transverse ribs 108 of V-shape that form corresponding V-shaped grooves 109 in the surface of the upper wall 102a of the housing 102. These grooves 109 are restricted to the side edge regions of the upper wall 102a and, when the track 101 is installed, face outwardly. As a result, the side edge regions have anti-slip characteristics that reduce the risk of passengers slipping when stepping on the track 101.

15 The compression may be applied across the full width of the track 101. For example, by replacing the rollers 105,106 with wider rollers or providing additional pairs of rollers between the rollers at the edges of the track. Alternatively, the track 101 may be inserted in a press or similar device for compressing the track transverse to its length.

20

Referring now to Figure 9, there is shown a modification to the insert 3,103 used in the tracks 1,101 above-described in which like reference numerals in the series 200 are used to indicate corresponding parts.

25

In this embodiment, the insert 203 is provided with a layer 203b of photoluminescent material overlaid with a fluid protective layer 203c of clear plastics or lacquer on each side of the aluminium base strip 203a. As a result, when the insert 203 is assembled in the housing 2,102, the track 1,101 can be fitted either way up to present a layer 203b of photoluminescent material uppermost.

30

This arrangement also enables a repair to be carried out by lifting a damaged section of track 1,101 and re-fitting the track 1,101 the other way up so that the underside becomes the topside and the damaged topside becomes the underside. This can be done without removing the insert 203 from the housing 2,102 and avoids having to re-seal the end of the track 1,101.

It will be understood this arrangement enables a repair to a damaged or worn section of the track 1,101 to be carried out quickly and easily by re-using the original section of the track 1,101. Thus, it is only necessary to carry out the following steps:-

- (a) lift the damaged section of track 1,101,
- (b) clean the underside to remove any adhesive originally used to secure the section of track 1,101 in place,
- (c) apply new adhesive to the worn or damaged topside, and
- (d) re-fit the section of track 1,101 with the topside now facing downwards and the underside facing upwards to present a new, clean undamaged surface outwards.

This can be done in a short period of time, for example during the normal turn around between flights thereby avoiding delays while repairs are effected. Furthermore, as the track section is re-fitted, no spare parts are required thereby reducing the risk of the aircraft being grounded through lack of suitable spare parts to effect a repair.

Where the insert 203 is used with the housing 102 of Figures 7 and 8, both rollers 105,106 (or other means employed to compress the housing 102) may be formed with transverse ribs 108 of V-shape. As a

result, corresponding V-shaped grooves 109 are formed in the surface of the upper wall 102a and the lower wall 102b of the housing 102.

5 In this way, the side edge regions of the track 101 have anti-slip characteristics on both the upper and lower surfaces. Thus, when a section of track 101 is reversed to effect a repair, the side edge regions of the new surface match the side edge regions of the surface of the existing adjacent sections of track 101.

10 Where both the upper and lower surfaces of the track 101 are formed with grooves 109, it is preferred to apply adhesive to the centre region of the track 101 between the side edge regions at least when the track 101 is originally fitted. As a result, the grooves 109 on the underside are not filled with adhesive which may be difficult to remove when lifting a
15 damaged section of track 101 that is to be reversed and re-fitted.

In this way, cleaning the underside of a section of track 101 which is lifted for reversing and re-fitting is facilitated. Moreover any dirt that may have penetrated under the track 101 and partially or completely filled
20 the grooves 109 will normally be easily removed when cleaning the underside to remove adhesive from the centre region between the grooves 109.

With reference now also to Figures 10 and 11, there is shown the general
25 layout of an emergency lighting system incorporating the track 1 in an aircraft 10.

The aircraft 10 has a plurality of rows of seats 11 disposed on either side of a main aisle 12 extending the length of the passenger compartment or
30 cabin 13.

A rear exit 10a is provided at the back of the cabin 13 and a pair of front exits 10b, 10c are provided on opposite sides of the cabin 13 at the front. The exits 10a, 10b, 10c are employed for passengers to get on and off the aircraft both in normal use and in an emergency.

5

A further pair of exits 10d, 10e are provided on either side of the cabin 13 approximately mid-way between the ends of the aisle 12, usually opening over the wings (not shown) of the aircraft 10 and which are only used in an emergency.

10

The emergency lighting is positioned on the floor along each side of the main aisle 12 adjacent to the aisle seats 11a to define an aisle path 14 extending from the rear exit 10a the length of the cabin 13 between the aisle seats 11a.

15

At the front of the cabin 13, the emergency lighting is positioned along each side of a pair of exit aisles 15, 16 extending from the main aisle 12 to the front exits 10b, 10c respectively.

20 Between the ends of the main aisle 12, emergency lighting is positioned on each side of another pair of exit aisles 17, 18 extending from the main aisle 12 to the centre exits 10d, 10e respectively.

25 In this way, the emergency lighting defines an escape route from any row of seats 11 in the cabin 13 along the main aisle 12 and exit aisles 15, 16, 17, 18 to the exits 10a, 10b, 10c, 10d, 10e.

30 The emergency lighting is provided by arranging pre-formed lengths of encapsulated track 1, for example 1 or 2 metre lengths, end to end or at right angles to each other. A pre-formed length of track 1 can also be cut into a shorter length and the cut end sealed to enable the emergency

lighting to be adapted to suit the layout of the seats and exits in a particular aircraft.

Each length of track 1 has the insert 3 extending between the ends so that,
5 when lengths of track 1 are laid end to end or at right angles, the light emitted by the inserts 3 is substantially unbroken along the escape route and provides a continuous cue from any region of the main and exit aisles to an exit.

10 As best shown in Figure 11, lengths of track 1 may incorporate markings 19 to show where the exit aisles 17, 18 lead from the main aisle 12 to the centre exits 10d, 10e. The markings 19 may be applied to the insert 3 and encapsulated within the track 1 during manufacture.

15 The markings 19 may be in the form of symbols such as arrows, chevrons or the like. Alternatively or additionally, the markings 19 may include words such as 'exit' or the like to reinforce the message provided by the symbols.

20 The markings 19 may be made visible by transmitting light of a different colour to the insert. For example the markings 19 may be applied using a dye that glows with light of a different colour to the rest of the insert 3. In this way, the light output of the insert 3 is not reduced.

25 Alternatively, the markings 19 may be made visible by blocking the light emitted by the insert 3. For example, the markings 19 may be applied using symbols and/or words that appear dark against an illuminated background.

30 Figures 12a through 12f show various types of self-adhesive markings 19 such as arrows, chevrons, words etc for use in the tracks 1,101 above-

described and Figures 13a through 13d show a method of attaching the markings.

5 The markings 19 are attached to the photoluminescent insert 3,103 after removal of a backing film 52 from the lower surface to expose the adhesive. Once applied, a protective application tape 53 is removed from the upper surface to expose the markings 19.

10 In this way, markings 19 can be provided at appropriate positions to indicate the direction to an exit and to identify the position of an exit. The markings 19 may be made visible by blocking the light emitted the insert 3,103 so as to appear dark against an illuminated background. Alternatively, the symbols 19 may be made visible by transmitting light of a different colour to the background.

15 Similar markings may be provided to indicate where the exit aisles 15, 16 lead from the main aisle 12 to the exits 10b, 10c at the front of the aircraft 10, and also to indicate where the main aisle 12 leads to the exit 10a at the rear of the aircraft 10.

20 By the use of such markings, people moving along the main aisle 12 are provided with an advance warning as they approach an exit aisle 15, 16, 17, 18 and, on reaching an exit aisle 15, 16, 17, 18, are directed into the exit aisle 15, 16, 17, 18 towards the exits 10b, 10c, 10d, 25 10e.

The size and/or spacing of the markings may alter as the junction between the main aisle 12 and the exit aisles 15, 16, 17, 18 is approached to provide a visual warning of the proximity of the exit aisles 15, 16, 17, 30 18. For example, the arrows 19 may become smaller and more closely spaced together nearer the exit aisles 15, 16, 17, 18.

As a result, people can enter an exit aisle 15, 16, 17, 18 from the main aisle 12 with confidence assisting the smooth flow of people towards the exits 10a, 10b, 10c, 10d, 10e and reducing congestion. This is particularly important in an emergency where people may be confused and start to panic if the track 1 does not provide a positive indication of the route to an exit 10a, 10b, 10c, 10d, 10e. In this way, evacuation of the aircraft is facilitated in a simple and effective manner.

- 10 The track 1 can be retrofitted to existing aircraft to replace electrical emergency lighting systems with a photoluminescent system, for example during refurbishment, or it can be fitted as original equipment to provide new aircraft with a photoluminescent emergency lighting system.
- 15 Where the track 1 is fitted to new aircraft, it is envisaged that the track 1 could be incorporated into the structure of the aircraft at an early stage of the production. For example, the track 1 could be fitted to the floor panels prior to assembly.
- 20 A particular feature of the track 1 according to the present invention is the low profile or depth of the track 1 such that it may be fitted in both carpeted and non-carpeted areas of the aircraft 10 with advantages for both the manufacture and installation of the track 1. In Figure 1, the track 1 is shown with the flooring material butted up against the flat sides of the track 1 and the flat upper surface of the track substantially flush with the flooring material.

In this way, installation of the track 1 does not present a safety hazard for passengers to trip over. Also, the upper surface of the track 1 is less susceptible to damage by people walking on the track 1 and/or from wheels of trolleys or cleaning equipment riding over the track 1.

Moreover, cleaning the floor in which the track 1 is laid is facilitated and there are no areas for dirt or liquid to become trapped and cover the track 1. The upper surface of the track 1 may be given a surface hardening treatment to increase the resistance to damage, especially
5 scratching which may impair the emission of light from the track 1.

It will be understood that the track 101 may be used in place of the track 1 with the lower profile produced by compressing the outer member 102 providing further benefits and advantages for installation of
10 the track 101 with a variety of different floor coverings.

Referring now to Figures 14 and 15, there is shown the arrangement of an emergency lighting system employing the track 1 of Figures 1 to 5 in an aircraft 20 having interchangeable demountable seat units 21 of different
15 width.

The aircraft 20 has rows of seats 22 in two sections. In a first section, each row has six seats, three on each side of the main aisle 23. In a second section, each row has four seats, two on each side of the main
20 aisle 23. The first section may be for economy class passengers and the second section for business class passengers.

Each group of three seats in the first section is provided by a demountable multi-seat unit 21a and each group of two seats in the second section is
25 provided by a demountable multi-seat unit 21b. The units 21a are wider than the units 21b and aisle 23 is narrower between the units 21a in the first section than between the units 21b in the second section.

The photoluminescent track 1 extending along each side of the aisle 23 is
30 arranged to identify the boundaries of the aisle 23 and the escape path defined therebetween is wider in the second section.

As a result, if the wider seat units 21a are fitted in the second section as shown in dotted outline in Figure 14 to increase the capacity of the aircraft 20, the width of the aisle 23 is reduced. This has the effect that
 5 the new boundary of the aisle 23 is no longer indicated by the existing track 1 which is now obscured by the wider seat units 21a. It will be understood this is but one example of the effect of changing one seating unit for another and that other arrangements and combinations of multi-seat units may give rise to the same problem.

10

To alleviate this problem without altering the layout of the existing track 1 on the floor of the aircraft 20, a photoluminescent track 24 is provided on the side of the aisle seat of the wider seat units 21a which overlie the floor track 1. In this way, the track 24 identifies the boundary
 15 of the aisle 23 and defines an escape path between the seat units which the passengers can follow to evacuate the aircraft 20.

As best shown in Figure 15, the aisle seat has a side panel 25 and the track 24 is located on the side facing the aisle at the bottom of the
 20 panel 25 close to the floor. The track 24 is formed by a strip of the insert 3 which can be mounted in a frame or carrier (not shown) releasably attached to the side panel 25 to overlie and protect the insert 3. The frame or carrier may be a moulding of a suitable transparent or translucent material, for example a plastic material such as polycarbonate.

25

The track 24 extends in the longitudinal direction of the aisle 23 and may be provided with markings such as arrows or words as described previously. The track 24 can be of different lengths depending on the size and/or shape of the side panel 25 to which it is fitted. In a
 30 modification (not shown), the track 24 is incorporated into the side

panel 25, for example the side panel 25 may be provided with a slot or recess to receive the insert 3.

Again, it will be understood that the track 1 may be replaced by the
5 track 101 and that the photoluminescent tracks 1, 101 and 24 above-described may be combined with other features to assist evacuation of the aircraft 10, 20 in an emergency. For example, the position of the exits 10a, 10b, 10c, 10d, 10e may be identified by photoluminescent material on the doors and/or more preferably on the door surround so that
10 the position of the exit can be identified with the door both closed and open. The handles and any instructions for opening the doors may also be identified and highlighted by the use of photoluminescent material.

As will be appreciated, the photoluminescent tracks 1, 101 and above-
15 described are 24 mounted at or near floor level and provide an escape route for passengers to follow if the cabin fills with smoke blocking light from any other source. In addition to these floor level tracks, photoluminescent tracks may also be provided at ceiling level to guide passengers to the exits without the presence of smoke in the cabin from a
20 fire or other source. For example, if the main lighting system fails at night or in conditions of low ambient light in the cabin in normal conditions or in an emergency. Thus, electrical emergency lighting systems with separate storage batteries, wiring connections and associated parts may be eliminated entirely by the use of a fully integrated
25 photoluminescent system for emergency lighting and exit identification.

It will be understood that the above-described embodiments are intended
to illustrate the diverse range and application of the invention and that
features of the embodiments may be used separately or in combination
30 with any other feature of the same or different embodiments to produce a

photoluminescent track that can be used as emergency lighting to identify an escape route.

- Moreover, while the specific materials and/or constructions of track
5 described and illustrated are believed to represent the best means
currently known to the applicant, it will be appreciated that the invention
is not limited thereto and that various modifications and improvements
can be made within the spirit and scope of the claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2